

Taping tool **KTHB Smart**



SMALLEST, ELECTRIC STATIONARY CABLE TAPING TOOL

KABATEC's smallest stationary taping tool with minimal space requirements. Made for fast, easy handling thanks to an open winding head controlled with a foot pedal.

Highest quality in an operator-guided process

- Consistent tape tension, guaranteed wrinkle-free taping
- Controlled, two-handed process thanks to the stationary machine

YOUR BENEFITS

Time savings thanks to simple and ergonomic handling

- Immediately ready for operation thanks to extremely easy installation and operation
- Operable in various work positions without major preparation or training
- Simple and fast integration into assembly lines
- Integrated cutting device

Efficient with shorter tape lengths

- Developed for production of shorter tape lengths and unit quantities
- Processes conventional adhesive tapes
- Wide processing spectrum of tape widths and roll sizes

Application	Taping from short to medium distances
Tape materials	All conventional adhesive tapes
Tape width	9 – 19 mm, optional 25 mm
Tape core diameter	1.5" and 3", optional 1.25" or 1"
Tape outer diameter	max. 110 mm
Taping diameter	3 – 25 mm
Rotational speed	120 – 380 rpm
Power supply	110 – 230 V, 50/60Hz
Working voltage	19 V DC
Dimensions (W×H×D)	150 × 250 × 256 mm
Weight	4.2 kg

KABATEC