



application	taping of simple cable kits and modules e.g. (door cable kits, mirror wiring, battery cable kits, roof cable kits, among others)
rotational speed	100 –1000 rpm, incl. winding head positioning unit
feed rate	0-40 mm/rotation
programming	via touch panel, 3 steps
cable/harnesses diameter	up to 20mm (or as per customer requirements)
tape width	9-19mm (or as per customer requirements)
material	any conventional adhesive tape
connection	1-phase 230V/50Hz, 6 bar compressed air
dimensions (H/B/T)	590 x 930 x 730 mm
weight	90 kg
device to reduce the unwind forces of the tape	optional
tape end detection	optional
device for using Alu-PVC-tape	optional
additional safety guard	optional

- The Taping Machine KTR 10 CS is a compact desktop machine
- It quickly and reliably completes the most diverse taping tasks.
- A combined system for length measurement and feed ensures a compact design and makes the KTR 10 CS an economic tool for your production of cable kits.
- A form or assembly board is no longer required in most cases.
- The selection of proven components for our machines guarantees virtually maintenance-free and reliable operation.
- Our machines are customized to your product according to the type and requirements of your application.
- This is possible because we can provide comprehensive inhouse services ranging from project management, design and production to customer service.

CHARACTERISTIC FEATURES

- Desktop Taping Machine
- Measurement system with 3 steps
- Pneumatic actuation of the feed roller (opening, closing)
- Winding head speed, max. 1000 rpm
- Winding head positioning
- Massive guard cover with clear view on to the winding table
- Ergonomic machine housing
- Armrest made of wood

