



DC2013-T Series

Resistance Spot Welding Power Supplies

The DC2013-T Series is a high performance resistance spot welding power supply, combining touch panel integrated database process control and monitoring with ultra high duty and low ripple 3000 A DC output.


Integrating state of the art technologies, these units take the concept of real-time SPC process control to unsurpassed levels, allowing welding database profiles to be stored, monitored and adjusted from anywhere in the world via TCP/IP Ethernet.

The internal database technology provides process and production engineers with a vast array of process control features by which to enhance production line quality control and monitoring methodologies.


KEY FEATURES:

- Power switching system provides unsurpassed levels of DC current with ultra low ripple and fast closed-loop response to react to and control challenging applications.
- High voltage outputs permit long cabling for automation and power distribution to multi-headed systems.
- Full TCP/IP interfacing to internal and external database systems.
- Associate and view PDF work instructions and process manuals with weld schedules
- Operator & Engineer Modes.
- Associate and view JPEG and BMP files with weld schedule for QC and process checking
- 3 USB ports: for USB memory stick, Mouse, Keyboard
- Built in graphical SPC functionality with optional displacement monitoring with dynamic weld control.
- Optional electrical system with E-Stop connectivity for automation.
- Weld head force control within weld schedules.
- 7" Color Touchscreen Panel Interface with context sensitive, intuitive menu system.
- High speed automation and communication ports with full remote control capability.


TYPICAL APPLICATIONS




Crimp weld connector




Pre Compacted Wire to Terminal



Projection Weld Switch Dashboard



Resistance weld engine motor armature



Stranded wire to coil



Stranded wire to terminal

OPTIONS:

- Optically isolated analog electrical channel monitoring
- DC2013-TD versions available with 1,3 or 6 channel weld displacement monitoring built-in and dynamic weld cutoff



Remote pendant option available on all models

TECHNICAL SPECIFICATIONS

Model	DC2013-T
Maximum Output Current	3000 Amps DC
Output Voltage at Full Load	6 VDC
Maximum Output Power	18 kW
Full Output Duty Cycle	3% @ 3000 A (2% @ 4000 A option)
Control Modes	Current/Voltage/Power
Output Accuracy of setting	± 1%
Ripple	<1%
Program Timing Values	Squeeze Time
	Upslope Time Pulse 1
	Peak Time Pulse 1
	Downslope Time Pulse 1
	Delay Time Between Pulses
	Upslope Time Pulse 2
	Peak Time Pulse 2
	Downslope Time Pulse 2
	Hold Time
Process Monitor Limits	Current/Voltage (Displacement)
Number of waveforms averaged	User defined
Waveform Window limiting range	0 - 100%
Waveform Window tolerances	0 - 100%
Optional feedback monitoring	Up to 6 channels of real time weld displacement monitoring
Displacement monitoring	LVDT or Encoder
Force Range	0 - 500 N (0-112 lb)
Input Requirements	3 phase
Input Voltage	380 - 480 VAC
Control I/O	Opto isolated
Serial Communications	Ethernet via TCP/IP, USB 2.0, RS232

WEIGHT & DIMENSIONS

Dimensions (L x W x H)	19.6 in x 8.7 in x 17.5 in (497 mm x 220 mm x 445 mm)
Weight	84 lb (38 kg)

Footnote- Also available in horizontal configuration. Ask factory for details.



AMADA WELD TECH INC.

1820 S. Myrtle Ave. • Monrovia, CA 91016 US
 T: (626) 303-5676
info@amadaweldtech.com • www.amadaweldtech.com
 ISO 9001 Certified Company • 24/7 Repair Service: 1-866-751-7378

AMERICAS

AMADA WELD TECH (Midwest Technical Center)
 Detroit, Michigan
 T: (248) 313-3078
midwestsales@amadaweldtech.com

AMADA WELD TECH DO LTDA.
 São Paulo, Brasil
 T: +55-11-4193-3607
antonio.ruiz@amadaweldtech.com

EUROPE

AMADA WELD TECH GmbH
 Munich, Germany
 T: +49-89-839403-0
info@amadaweldtech.eu

ASIA

AMADA WELD TECH CO., LTD.
 Isehara, Japan
 T: +81-4-7125-6177
sales@miyachi.com

AMADA WELD TECH KOREA CO., LTD.
 Seoul, Korea
 T: +82-31-8015-6810
sales@amadaweldtech.co.kr

AMADA (THAILAND) CO., LTD.
 Bangkok, Thailand
 T: +66-2170-5900
info@amada.co.th

AMADA WELD TECH INDIA PVT., LTD.
 Bangalore, India
 T: +91-80-4092-1749
info@miyachiindia.com

AMADA WELD TECH (Mexico Office)
 El Paso, Texas
 T: (915) 881-8765
mxsales@amadaweldtech.com

AMADA WELD TECH SHANGHAI CO., LTD.
 Shanghai, China
 T: +86-21-6448-6000
jwu@msc.miyachi.com

AMADA WELD TECH TAIWAN CO., LTD.
 Taipei, Taiwan
 T: +886-2-2585-0161

AMADA VIETNAM CO., LTD.
 Ha Noi, Vietnam
 T: +84-4-6261-4583

Specifications subject to change without notice. Copyright© 2020 AMADA WELD TECH INC. The material contained herein cannot be reproduced or used in any other way without the express written permission of AMADA WELD TECH INC. All rights reserved.

